

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>G02F 1/133</b>		<b>A2</b>	(11) International Publication Number: <b>WO 00/02083</b> (43) International Publication Date: 13 January 2000 (13.01.00)
<p>(21) International Application Number: PCT/SE99/01094</p> <p>(22) International Filing Date: 17 June 1999 (17.06.99)</p> <p>(30) Priority Data: 9802460-7                      6 July 1998 (06.07.98)                      SE</p> <p>(71) Applicant: TELEFONAKTIEBOLAGET LM ERICSSON [SE/SE]; S-126 25 Stockholm (SE).</p> <p>(72) Inventor: LUTNAES, Sturla; Ulleråkersvägen 64, S-756 43 Uppsala (SE).</p> <p>(74) Agents: SVANFELDT, Hans-Åke et al.; Dr. Ludwig Brann Patentbyrå AB, P.O. Box 1344, S-751 43 Uppsala (SE).</p>			<p>(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b> <i>Without international search report and to be republished upon receipt of that report.</i></p>
<p>(54) Title: LCD TEMPERATURE SENSING</p> <p>(57) Abstract</p> <p>The temperature of a LCD (43), for example provided in a mobile telephone (41), is measured by covering the LCD (43) with a conductive touch screen bottom sheet (42) having known resistance-temperature relationship. A temperature stable resistor (44) is connected to the touch screen bottom sheet (42), and a voltage is applied over the resistor and the sheet. The voltage signal between the resistor (44) and the touch screen bottom sheet (42) is measured and converted into digital representation by an A/D-converter (45). The measured voltage signal is used to calculate the temperature of the touch screen bottom sheet which is substantially equal to the temperature of the LCD (43).</p>			
<p>The diagram illustrates a mobile telephone (41) with an LCD (43) on its front face. The LCD is covered by a conductive touch screen bottom sheet (42). A resistor (44) is connected to the sheet. An A/D-converter (45) and a microcontroller (46) are shown, connected to the resistor and the sheet. The telephone has a keypad and an antenna.</p>			

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**Title**

LCD temperature sensing

**Technical field of the invention**

5 The invention concerns a device for measuring the temperature near the liquid crystals of a liquid crystal display (LCD), and more specifically a device for measuring the temperature near the liquid crystals of a liquid crystal display (LCD) covered with a touch screen.

10 **Description of related art**

There is a growing market for electronic devices of the type having a LCD display for displaying visual information and a touch screen covering the LCD by which the user communicates with the device.

15 Liquid crystals are characterized by their ability to change their optical properties in response to applied electromagnetic fields. This has made them ideal for displaying altering information, such as in liquid crystal displays (LCD). This ability is affected by the temperature of the liquid crystals, which in its turn is dependent on a number of factors, such as air  
20 temperature, radiation from the sun, heat generated by electronic equipment in the vicinity of the display etc. The effects of varying LCD temperature is especially pronounced when the optical state of the liquid crystals is determined by low-voltage multiplexing technique, since this puts high requirements on the flexibility of the crystals.

25

It is therefore desirable to determine as close as possible the actual temperature of the liquid crystals. To obtain as good an estimation as possible of the temperature of the liquid crystals a temperature sensor should be disposed as near the liquid crystals as possible. Numerous  
30 patents are concerned with this task.

For example, the abstract of the Japanese patent JP-A-9-160001 describes a LCD control system wherein the contrast of the LCD is controlled by way of measuring the ambient temperature, and adjusting the contrast after comparing the measured temperature to a stored temperature and a contrast setting associated with the stored temperature. A similar system is also described in the abstract of the Japanese patent JP-A-8-114785. Such a control system has the disadvantage that the contrast adjustment is based on an ambient temperature that may differ considerably from temperature of the liquid crystals. This is the case regardless of whether the temperature is measured outside of the equipment in which the LCD is mounted, or inside the housing of the equipment.

It is also known, for example through JP-A 9-258161, to attach a small thermocouple sensor on a LCD display in order to measure its temperature. However, this has the disadvantage that only a point estimation of the LCD temperature is obtained. Therefore, considerable errors could occur, for example in a case where sunlight falls on only a part of the equipment.

Furthermore, through the Japanese patent publication No. 54-064998 it is known to cover a surface of a LCD display with a tin oxide film, and measuring the resistance of the tin oxide film to determine the temperature of the LCD. The tin oxide film may also act as a heating means, to provide a suitable operation temperature to the liquid crystals. If practiced in conjunction with a touch screen, this invention has the disadvantage that even a highly transparent additional temperature sensing layer would undesirably reduce the visual contrast of the LCD. Since the touch screen that covers the LCD causes a certain loss of contrast and brilliance in itself, it is generally not desirable to cover the LCD with yet another transparent sheet.

**Summary of the invention**

It is a general object of the invention to provide a device for measuring the temperature of a LCD provided with a touch screen, wherein the measurement is performed within the touch screen very near the liquid crystals and gives an integral temperature estimation substantially over the entire LCD area.

This and other objects are achieved by the invention as defined in the accompanying claims.

Thus, in a first aspect of the present invention there is provided a device for measuring the temperature of a LCD provided with a touch screen.

According to this aspect of the invention, one of the sheets constituting the touch screen, namely the bottom sheet being disposed adjacent to the LCD surface, is provided with a transparent conductive layer having a known relationship between temperature and its electrical resistance. At selected intervals the resistance of the transparent layer is measured and interpreted as the temperature of the touch screen bottom sheet.

As the touch screen bottom sheet is in thermal contact with the LCD surface, and as the LCD glass sheet that parts the liquid crystals from the touch screen bottom sheet has excellent heat conductivity, the temperature of the touch screen bottom represents a good estimation of the temperature of the liquid crystals of the LCD.

Furthermore, as the touch screen bottom sheet covers substantially the entire LCD area the measured electrical resistance of the touch screen bottom sheet represents an overall estimation which, in cases of uneven temperature distribution, is an integral measure of both warmer and cooler areas on the LCD.

In general, the components necessary to carry out the invention are already present in a LCD/touch screen assembly. Any additional components are of low cost and are easy to assemble, thereby providing for  
5 cost effective production.

Apart from being cost effective, the invention makes it unnecessary to provide an additional temperature sensing transparent sheet in addition to the touch screen, thereby avoiding an undesired reduction in the visual  
10 contrast of the LCD.

Thus, the present invention shows a number of advantages, such as:

- high precision estimation of the liquid crystal temperature as the temperature measurement is made very near the liquid crystals,
- 15 - temperature measurement that is sensitive to temperature gradients across the LCD display, since the measurement is made across the entire LCD surface,
- cost efficiency due to few new components, said components being cheap and easy to assemble, and
- 20 - combination of the temperature sensor with the already present touch screen avoids further contrast losses.

In a second aspect of the present invention is provided a method for manufacturing a device according to the invention.  
25

**Brief description of the drawings**

The present invention will now be described, by way of examples only, with reference to the attached drawings, wherein:

5 Fig. 1 is a schematic sectional side view of a LCD and touch screen assembly for use with the present invention.

Fig.2 is a diagram showing the relationship between electrical resistance (R) for a polyethylene terephthalate film and temperature (T).

10

Fig. 3 is a circuit diagram showing a typical conventional circuit for use with a touch screen.

15 Fig. 4 is a circuit diagram of a LCD temperature measuring device according to the invention combined with a touch screen.

Fig. 5 is a simplified circuit diagram showing resistances and voltages of a temperature measuring device according to the invention.

20 Fig. 6 is a schematic block diagram of a circuit for adjustment of a LCD display.

Fig. 7 is a schematical, partly transparent sketch of a mobile phone comprising a according to the invention.

25

Fig. 8 is a flow chart illustrating a method for manufacturing a LCD temperature measuring device according to the invention.

30 It should be noted that same reference numbers in different figures relates to same components.



**Detailed description of embodiments**

An embodiment of a the present invention shall now be described.

Fig. 1 is a schematic sectional side view of a typical conventional  
5 LCD/touch screen assembly suitable for use with the present invention.  
The assembly includes a touch screen 20 covering a liquid crystal display  
(LCD) 2. The LCD 2 comprises a top glass sheet 3, a bottom glass sheet 4,  
and distance elements 5 and liquid crystals 6 disposed between the top  
and bottom glass sheets. Typically, the LCD is attached to a PC board (not  
10 shown). The touch screen 20 comprises a top sheet 21, a bottom sheet 22  
and spacers 23. The touch screen 20 could be fixed to the LCD top glass  
sheet 3 by means of an adhesive layer 9, as shown, provided that the  
adhesive layer has good thermal conductivity. However, in order to ensure  
best possible thermal conductivity between the top glass sheet and the  
15 touch screen bottom sheet it is preferred that the touch screen is disposed  
directly onto the LCD.

The top sheet 21 of the touch screen 20 is typically made from a plastic  
material, such as a polyester film. The bottom sheet 22 is typically made  
20 from a plastic material, such as a polyester film, or a glass sheet. On the  
inner surfaces, i.e. the surfaces facing each other, the sheets 21, 22 are  
covered with a conductive layer, typically indium tin oxide 24, 25,  
respectively. Thus, when the user presses the touch screen, thereby  
contacting the top and bottom sheets, i.e. the conductive layers 24, 25 of  
25 the sheets, an electrical voltage signal can be transferred through the  
conductive layers 24, 25.

Conventionally, a typical touch screen 20 is connected to the equipment at  
hand as in the example of a circuit diagram illustrated in fig. 3. A control  
30 unit (not shown, but indicated by the circuit lines CTRL) opens and closes  
the switches 31, 32, 33, 34, 35. An analog-to-digital (A/D) converter 36 is



provided to convert measured voltage values from analog to digital representation.

As the function of a touch screen is not in itself the subject of the present invention, it shall be described only very briefly by way of example as a background to the understanding of the invention.

When the user presses the touch screen at a certain point, the top and bottom sheet conductive layers 24 and 25 are short circuited at that point, as described above. For determining the position of this point, the control unit first closes the switches 31 and 32 to provide a voltage  $V_{cc}$  across the conductive layer 24 of the touch screen top sheet 21, opens the switches in 33 and 34 and puts the switch 35 in a state connecting the A/D-converter 36 to the conductive layer 25 of the touch screen bottom sheet 22 via connection point 38. A first voltage, the magnitude of which is dependent on the position where the user has short circuited the touch screen, is output by the A/D-converter to any suitable registering means. This first voltage gives a representation of the vertical position (when viewed in fig. 3) of the area pressed by the user. In a subsequent step the control unit opens switches 31 and 32, closes switches 33 and 34 and puts the switch 35 in a state connecting the A/D-converter 36 to the touch screen top sheet 21. The corresponding transverse position of the area pressed by user is then determined in an analogous way.

According to the invention, the temperature of the liquid crystals can be obtained by determining the temperature of the touch screen bottom sheet. This is achieved, according to the invention, by introducing a temperature stable resistor  $R_s$  in series with the conductive layer 25 of the touch screen bottom sheet 22, whereby the conductive layer has a temperature dependent resistance  $R_{ts}$ . At selected intervals a voltage  $V_{cc}$  is applied over the series of the resistor  $R_s$  and the touch screen bottom

sheet ( $R_{ts}$ ), and the voltage level  $V_{ts}$  between the resistor  $R_s$  and the touch screen bottom sheet  $R_{ts}$  is measured.

This is illustrated in the simplified circuit diagram of fig. 4, which  
5 corresponds to the conventional circuit of fig. 3, showing a circuit according to the invention wherein a temperature stable resistor 37 having a resistance  $R_s$  is disposed between the switch 34 and the connection point 38. The conductive layer 25 of the touch screen bottom sheet 22 has a temperature sensitive resistance  $R_{ts}$ . A voltage  $V_{ts}$  between the resistor  
10 37 and the touch screen bottom sheet 22 is measured at the connection point 38. This is illustrated in the schematical diagram of fig. 5.

Now the control unit (not shown) is programmed to, at selected intervals between its normal operation as described above, open switches 31 and  
15 32, close switches 33 and 34 to provide a voltage  $V_{cc}$  across the resistor 37 and the bottom sheet conductive layer 25 and put switch 35 in a state connecting the A/D-converter 36 to the connection point 38 between the resistor 37 and the bottom sheet conductive layer 25.

20 Knowing the applied voltage  $V_{cc}$ , the measured voltage  $V_{ts}$  and the resistance  $R_s$  of the temperature stable resistor, the temperature of the touch screen bottom sheet is calculated, for example by using Ohm's law:

$$R_{ts} = V_{ts} \cdot R_s / (V_{cc} - V_{ts}) \quad (1)$$

25 According to the invention, if the relationship between the electrical resistance and the temperature of the conductive layer 25 of the touch screen bottom sheet 22 is known, the resistance  $R_{ts}$  is useful to determine the temperature of the sheet 22. For a given material, such as a specific polyester film covered with indium tin oxide, this relationship could be  
30 available from the manufacturer of the film material. Otherwise, it is easily established by simply measuring the electrical resistance of a sample of

the material at a selected set of temperatures corresponding to the temperatures at which the LCD is specified to operate.

An example of this is shown in the diagram of fig. 2, which shows the relationship between electrical resistance (R) of a polyethylene terephthalate film covered with a conductive layer, and temperature (T). From the curve of the diagram it is apparent that the electrical resistance R of this particular film changes significantly within a temperature range from appr. -20 °C to +10 °C making it possible to establish a rather reliable relationship between temperature and resistance. At temperatures above appr. +10 °C a less reliable relationship can be established. Thus, with regard to the invention the polyethylene terephthalate film of fig. 2 is suitable for use in applications wherein the operating temperature of the liquid crystals is within the range of -20 °C through +10 °C.

15

Therefore, in order to decide which material to use for the bottom sheet of the touch screen it is necessary to estimate the operating temperature of the LCD to which the present invention is to be applied. Typically, the ambient temperature specified for the equipment that includes the LCD, e.g. a mobile phone or a portable computer, could be used as an approximation of the operating temperature.

20

Using equation (1) and a resistance-temperature diagram similar to that of fig. 2 for the material currently used in the transparent sheet, the temperature of the touch screen bottom sheet 22 is determined. Since the top glass sheet 3 of the LCD has excellent heat conductivity, the temperature of the touch screen bottom sheet 22 is a good estimation of the temperature of the liquid crystals 6.

25

Thus, the temperature of the liquid crystals 6 can be estimated with good accuracy by measuring the voltage  $V_{ts}$  between the resistor 37 and the touch screen bottom sheet conductive layer 25.

5 This procedure is well suited for automation, since the relationship between temperature and resistance of the touch screen bottom sheet can easily be transformed to an equation for implementation into a computer program being executed in a suitable micro processor. A computer program is also useful to control the measuring of  $V_{ts}$  and to calculate the  
10 resistance of the touch screen bottom sheet  $R_{ts}$ .

With the invention, a good estimation of the LCD temperature is obtained with already present components, such as the touch screen, due to the close contact between the touch screen bottom sheet and the LCD. Only  
15 one more component - a cheap resistor - and a non-complicated reprogramming of the control unit is necessary.

Also, as no additional transparent layers are added, no additional contrast loss is obtained.

20

Furthermore, as the touch screen covers the entire LCD surface any irregularities in the temperature distribution across the display surface are smoothed out since the measured resistance is an overall value taken over the entire touch screen bottom sheet. Thereby, a proper mean value for  
25 use when determining a temperature induced contrast adjustment of the LCD is provided, rather than a point estimation.

In order to illustrate the use of the temperature sensing element according to the present invention to adjust the contrast of a LCD, fig. 6 shows a  
30 schematic block diagram of a circuit for adjustment of a LCD display.

According to fig. 6, a TEMPERATURE SENSING ELEMENT, generally in the form of a touch screen bottom sheet acting in cooperation with a temperature stable resistor, is arranged in connection with a LC DISPLAY, as described above, to output a voltage signal  $V_{ts}$ . The voltage signal  $V_{ts}$  is transferred to a DISPLAY CONTROL, for example a designated preprogrammed microprocessor or a part of an overall control unit. The DISPLAY CONTROL responds to the applied voltage  $V_{ts}$  with a LCD control voltage signal  $V_{lcd}$  that is transferred to the LC DISPLAY. However, contrast adjustment of a LCD is in itself conventional and well known to those skilled in the art, and therefore no further explanation is given on this matter in the present description.

The present invention is particularly useful for LCD's that are used for displaying visual information in mobile electronic units, such as mobile telephones, hand held computers etc.

For example, fig. 7 schematically illustrates a mobile phone 41 provided with a LCD 43 and a touch screen 42 covering the LCD, whereby the touch screen bottom sheet is conductive, and acts as a temperature sensing element. The electronic unit of the mobile phone 41 comprises a temperature stable resistor 44, an A/D-converter 45 connected between the resistor 44 and the conductive layer of the touch screen bottom sheet 42 and a control unit 46 connected to the A/D-converter 45. The control unit 46 is programmed to perform the calculations described above. It should be noted that for simplicity voltage sources, ground potential terminals and contrast adjustment components are not shown, since these components are conventional and their use is very familiar to anyone skilled in the art. A mobile phone according to fig. 9 has the advantage that the user is presented with a LCD that always shows information in good light contrast, regardless of the ambient temperature as well as the internal temperature of the mobile phone.

A similar arrangement is useful for a hand held computer.

Fig. 8 is a flow chart illustrating the steps of a method for producing a LCD  
5 temperature sensing touch screen assembly according to the present invention. The method includes the steps of:

- covering a liquid crystal display (LCD) with a touch screen, as illustrated at 101, whereby the touch screen has a bottom sheet covered with a conductive layer as described above;
- 10 connecting a temperature stable resistor to the conductive layer on the touch screen bottom sheet, as illustrated at 102;
- providing a measuring terminal between the temperature stable resistor and the conductive layer of the touch screen bottom sheet, as illustrated at 103; and
- 15 providing a control unit for monitoring a voltage between the temperature stable resistor and the conductive layer of the touch screen bottom sheet, as illustrated at 103, whereby said voltage occurs in response to a voltage applied over the series of the temperature stable resistance and the conductive layer of the touch screen bottom sheet.

20

It should be understood that the scope of the present invention is not limited to the examples of embodiments described above, but is defined by the scope of the appended patent claims.

25



## CLAIMS

1. A device for measuring the temperature of a liquid crystal display (LCD) (2) by using a temperature dependent conductive layer (25) covering  
5 the LCD,  
**characterized in that** the conductive layer (25) constitutes a part of a touch screen (20) applied to the LCD (2), and said device comprises means (37, 38) for measuring an electrical property of the transparent layer (25) of the touch screen (20), the value of said electrical property being  
10 representative of an estimation of the temperature of the LCD.
2. The device according to claim 1,  
**characterized in that** said electrical property is the electrical resistance of the transparent layer (25) or the voltage over the transparent layer.  
15
3. The device according to claim 1 or 2,  
**characterized in that** said means for measuring said electrical property comprises:  
- a temperature stable resistor (37) connected to the transparent layer (25);  
20 and  
- a measuring terminal (38) arranged between the transparent layer (25) and said temperature stable resistor (37) for measuring a voltage signal (Vts) being representative of the temperature of the transparent layer and acting as an estimation of the temperature of the LCD (2).  
25
4. The device according to claim 3,  
**characterized in that** it further comprises a control unit for monitoring said voltage signal (Vts) and for adjusting the contrast level of the LCD (2) in response to said voltage signal (Vts).




5. A mobile telephone (41) having a liquid crystal display (LCD) (43),  
**characterized in that** it comprises a device according to any of the  
previous claims, for measuring the temperature of the LCD.
- 5 6. A portable computer having a liquid crystal display (LCD) (43),  
**characterized in that** it comprises a device according to any of the  
previous claims, for measuring the temperature of the LCD.
7. A method for manufacturing a device for determining the temperature  
10 of a liquid crystal display (LCD),  
**characterized in that** it comprises the steps of:  
- covering (101) the LCD with a touch screen, said touch screen having a  
sheet arranged in heat conducting relationship to the LCD;  
- providing means (102-104) for measuring an electrical property of said  
15 sheet, the value of said electrical property being representative of the  
temperature of the LCD.
8. The method according to claim 7,  
**characterized in that** said step of providing means for measuring an  
20 electrical property of the touch screen sheet comprises the steps of  
- connecting (102) a temperature stable resistor to the sheet; and  
- providing (103) a measuring terminal between the sheet and said  
temperature stable resistor.
- 25 9. The method according to claim 7,  
**characterized in that** said step of providing means for measuring an  
electrical property of the touch screen sheet comprises the step of  
providing (104) a control unit for monitoring a voltage signal at said  
measuring terminal.


1/5

*Fig. 1**Fig. 2*

2/5





*Fig. 3*  
*(Prior art)*




*Fig. 4*

3/5


*Fig. 5**Fig. 6*

4/5



*Fig. 7*

5/5

*Fig. 8*